



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001271906 A**

(43) Date of publication of application: 05.10.01

(51) Int. Cl. **F16H 41/30**  
**G01L 19/00**

(21) Application number: 2000087620

(22) Date of filing: 27.03.00

(71) Applicant: **KOMATSU LTD**

(72) Inventor: FUKUNO TOSHIHIRO  
TOYAMA MAKOTO

**(54) INTERNAL PRESSURE DETECTION METHOD  
FOR FLUID-POWER- MECHANICAL POWER  
CONVERTER, INTERNAL PRESSURE  
DETECTION DEVICE, AND TORQUE CONVERTER  
PROVIDED WITH INTERNAL PRESSURE  
DETECTION DEVICE**

COPYRIGHT: (C)2001,JPO

本発明の発露形態による、ロタアプタラックのタラッチャの構造図

**(57) Abstract:**

**PROBLEM TO BE SOLVED:** To provide an internal pressure detection device low in cost and a high in durability.

**SOLUTION:** A communication port 17 is provided between a junction 14a on a supply pipe supplying fluid and a junction 15a on a discharging pipe discharging fluid, two restrictors 12, 13 in the communication port 17 and a pressure sensor 11 located between the two restrictor 12, 13 are provided and a detected value of the sensor 11 is defined as an inner pressure of an object for pressure detection.

